sachsenkabel
an Amphenol company

Data Sheet

LC Connector - Huber+Suhner

Version:11.06.2024

Manufacturer	Huber+Suhner AG	
Compliance	IEC 61754.20, TIA 604-10-B	
Features	Small Form Factor (SFF) connector	
	With Simplex Push-Pull HD Clip	
Ferrule	Ø1,25 mm, zirkonia, axially spring-loaded	
Mating cycles	1,000	
Strain relief	≥ 100 N	
Temperature range	Operating temperature	-40°C up to +85°C
	Storage temperature	-40°C up to +85°C

Singlemode APC 8°

Housing material	Plastic / Black
Clip material	Plastic / Green
Fiber type	E9 / 125 µm (OS2 SMF28U)
Typical insertion loss	≤ 0,12 dB (Grade B)
Return loss	≥ 70 dB

LWL-Sachsenkabel GmbH
Hauptstraße 110, D-09390 Gornsdorf • Telefon +49 (0) 3721 / 39 88-0, Fax +49 (0) 3721 / 39 88-16 • info@sachsenkabel.de, www.sachsenkabel.de • Amtsgericht Chemnitz, HRB 58 62
Geschäftsführer Dr. Michael Müller, Craig Lampo, Adam Norwitt • USt-Id. DE 141 294 898 Bankverbindung Commerzbank • BIC COBADEFFXXX, IBAN DE98 6204 0060 0312 1860 00

Unverbindliches Datenblatt, Druckfehler, Irrtümer, Änderungen vorbehalten